

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring

Condition D.1.17 Record Keeping Requirements (c)

PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: <i>Ted Compton</i>	
Date of Inspection: <i>11/1/12</i>	Time: <i>1700</i>
Shift: (First or Second) <i>First</i>	
Monitor ID: <i>MiniRae 2000</i>	
Instrument Calibration Gases: <i>Isobutylene 100PPM</i>	
Background Instrument Reading: <i>0.0</i>	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
	Running	Down					Y/N	Date	Time	
Vapor Recovery System:	Running	Down	—	—		A	N	—	—	—
CARBON OR FLARE*	✓									
SDS Shredder	Running	Down	301	0		A	N	—	—	—
ATDU / OWS	Running	Down	2018	2.0	0	A	N	—	—	—
Area 8 -- Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	3765	1.3	0	A	N	—	—	—
Distillation Unit	Running	Down	3555	4.0	0	A	N	—	—	—
Tank 51	Running	Down	1286	1.3	0	A	N	—	—	—
Tank 55	Running	Down	2401	1.1	0	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring

Condition D.1.17 Record Keeping Requirements (c)

PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: <u>Ted Compton</u>	
Date of Inspection: <u>1/2/12</u>	Time: <u>1700</u>
Shift: (First or Second) <u>First</u>	
Monitor ID: <u>MiniRae 2000</u>	
Instrument Calibration Gases: <u>Isobutylene 100ppm</u>	
Background Instrument Reading: <u>0.0</u>	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
	Running	Down					Y/N	Date	Time	
Vapor Recovery System:	Running ✓	Down	—	—		A	N	—	—	—
CARBON OR FLARE*	Running ✓	Down	274	0		A	N	—	—	—
SDS Shredder	Running ✓	Down	1936	2.4	0	A	N	—	—	—
ATDU / OWS	Running ✓	Down	3518	1.7	0	A	N	—	—	—
Area 8 -- Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	3331	4.1	0	A	N	—	—	—
Distillation Unit	Running ✓	Down	1447	1.5	0	A	N	—	—	—
Tank 51	Running ✓	Down	2631	1.3	0	A	N	—	—	—
Tank 55	Running ✓	Down								

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring

Condition D.1.17 Record Keeping Requirements (c)

PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Rick PALOMO	
Date of Inspection: 1/4/12	Time: 5:00 AM
Shift: (First or Second) Second	
Monitor ID: Mini Rae 2000	
Instrument Calibration Gases: 150 BUTYLENE 100 PPM	
Background Instrument Reading: 0.0	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
	Running	Down					Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	—	—		A	N	—	—	—
SDS Shredder	Running ✓	Down	175	0		A	N	—	—	—
ATDU / OWS	Running ✓	Down	1951	2.3	0	A	N	—	—	—
Area 8 -- Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	1302	0	5.1	A	N	—	—	—
Distillation Unit	Running ✓	Down	3951	1.3	0	A	N	—	—	—
Tank 51	Running ✓	Down	4250	0	2.3	A	N	—	—	—
Tank 55	Running ✓	Down				A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring

Condition D.1.17 Record Keeping Requirements (c)

PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: <u>James A Garcia</u>	
Date of Inspection: <u>1/04/12</u>	Time: <u>5:00 pm</u>
Shift: (First or Second) <u>First</u>	
Monitor ID: <u>MMI/Pace 2000</u>	
Instrument Calibration Gases: <u>Isobutylene 100ppm</u>	
Background Instrument Reading: <u>0.0</u>	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
	Running	Down					Y/N	Date	Time	
Vapor Recovery System:	Running ✓	Down	—	—	—	A	N	—	—	—
CARBON OR FLARE	Running ✓	Down	270	0	—	A	N	—	—	—
SDS Shredder	Running ✓	Down	1941	2.6	0	A	N	—	—	—
ATDU / OWS	Running ✓	Down	3521	1.4	0	A	N	—	—	—
Area 8 -- Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	3328	4.3	0	A	N	—	—	—
Distillation Unit	Running ✓	Down	1445	1.2	0	A	N	—	—	—
Tank 51	Running ✓	Down	2631	1.2	0	A	N	—	—	—
Tank 55	Running ✓	Down								

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring

Condition D.1.17 Record Keeping Requirements (c)

PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: <u>Rick PALOMO</u>	
Date of Inspection: <u>1/5/12</u>	Time: <u>5:00 AM</u>
Shift: (First or Second) <u>Second</u>	
Monitor ID: <u>Mini Rgc 2000</u>	
Instrument Calibration Gases: <u>ISOBUTYLENE 100 PPM</u>	
Background Instrument Reading: <u>0.0</u>	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust	Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
	Running	Down				Y/N	Date	Time	
Vapor Recovery System:	Running	Down	—	—	A	N	—	—	—
CARBON OR FLARE*	✓								
SDS Shredder	Running	Down			A	N	—	—	—
	✓								
ATDU / OWS	Running	Down			A	N	—	—	—
	✓								
Area 8 -- Tanks 52,53,54 (Tanks 02 through 04)	Running	Down			A	N	—	—	—
	✓								
Distillation Unit	Running	Down			A	N	—	—	—
	✓								
Tank 51	Running	Down			A	N	—	—	—
	✓								
Tank 55	Running	Down			A	N	—	—	—
	✓								

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring

Condition D.1.17 Record Keeping Requirements (c)

PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: <u>RICK PALOMO</u>	
Date of Inspection: <u>1/5/12</u>	Time: <u>5:00 AM</u>
Shift: (First or Second) <u>Second</u>	
Monitor ID: <u>Mini Rac 2000</u>	
Instrument Calibration Gases: <u>ISOBUTYLENE 100 PPM</u>	
Background Instrument Reading: <u>0.0</u>	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
	Running	Down					Y/N	Date	Time	
Vapor Recovery System:	Running	Down	—	—		A	N	—	—	—
CARBON OR FLARE*	✓									
SDS Shredder	Running	Down	137	0		A	N	—	—	—
ATDU / OWS	Running	Down	1541	0	2.3	A	N	—	—	—
Area 8 -- Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	1351	1.9	0	A	N	—	—	—
Distillation Unit	Running	Down	3451	0	5.7	A	N	—	—	—
Tank 51	Running	Down	3002	2.1	0	A	N	—	—	—
Tank 55	Running	Down	3905	0	1.9	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring

Condition D.1.17 Record Keeping Requirements (c)

PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: <i>Alma N. Garcia</i>	
Date of Inspection: <i>1/05/12</i>	Time: <i>5:00 pm</i>
Shift: (First or Second) <i>First</i>	
Monitor ID: <i>Mini Rave 2000</i>	
Instrument Calibration Gases: <i>Isobutylene 100ppm</i>	
Background Instrument Reading: <i>0.0</i>	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System:	Running	Down	—	—		A	N	—	—	—
CARBON OR FLARE*	✓		—	—		A	N	—	—	—
SDS Shredder	Running	Down	273	0		A	N	—	—	—
ATDU / OWS	Running	Down	1938	2.7	0	A	N	—	—	—
Area 8 -- Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	3517	1.2	0	A	N	—	—	—
Distillation Unit	Running	Down	3331	4.5	0	A	N	—	—	—
Tank 51	Running	Down	1450	1.3	0	A	N	—	—	—
Tank 55	Running	Down	2632	1.1	0	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring

Condition D.1.17 Record Keeping Requirements (c)

PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: <u>Rick Palomo</u>	
Date of Inspection: <u>1/6/12</u>	Time: <u>5:00 AM</u>
Shift: (First or Second) <u>Second</u>	
Monitor ID: <u>Mini Pac 2000</u>	
Instrument Calibration Gases: <u>ISOBUTYLENE 100PPM</u>	
Background Instrument Reading: <u>0.0</u>	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust	Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
	Running	Down				Y/N	Date	Time	
Vapor Recovery System:	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	—	—	A	N	—	—	—
CARBON OR FLARE*	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	—	—	A	N	—	—	—
SDS Shredder	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	175	0	A	N	—	—	—
ATDU / OWS	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	2151	0 5.1	A	N	—	—	—
Area 8 -- Tanks 52,53,54 (Tanks 02 through 04)	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	1351	2.1 0	A	N	—	—	—
Distillation Unit	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	1955	0 5.8	A	N	—	—	—
Tank 51	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	2301	0 2.3	A	N	—	—	—
Tank 55	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	2505	9.1 0	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring

Condition D.1.17 Record Keeping Requirements (c)

PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: <u>R Long</u>	
Date of Inspection: <u>11/7/12</u>	Time: <u>5AM</u>
Shift: (First or Second) <u>Second</u>	
Monitor ID: <u>Mini RAE 2000</u>	
Instrument Calibration Gases: <u>ISOBUTYLENE 2000</u>	
Background Instrument Reading: <u>0.0</u>	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust	Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
	Running	Down				Y/N	Date	Time	
Vapor Recovery System:	Running	Down	—	—	A	N	/	/	
CARBON OR FLARE*	✓								
SDS Shredder	Running	Down	300	0.0	A	N	/	/	
ATDU / OWS	Running	Down	2050	7 0.0	A	N	/	/	
Area 8 -- Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	1770	2 0.0	A	N	/	/	
Distillation Unit	Running	Down	3300	4 0.0	A	N	/	/	
Tank 51	Running	Down	1440	2 0.0	A	N	/	/	
Tank 55	Running	Down	1300	2 0.0	A	N	/	/	

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring

Condition D.1.17 Record Keeping Requirements (c)

PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: M. Torres

Date of Inspection: 1-8-12

Time: 6:00 am

Shift: (First or Second) Second

Monitor ID: Mini Roc 2000

Instrument Calibration Gases: ISO Butylene

Background Instrument Reading: 0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust	Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
	Running	Down				Y/N	Date	Time	
Vapor Recovery System:	Running	Down	—	—	A	N	—	—	—
CARBON OR FLARE*	Running	Down	276	0	A	N	—	—	—
SDS Shredder	Running	Down	276	0	A	N	—	—	—
ATDU / OWS	Running	Down	1930	24	A	N	—	—	—
Area 8 -- Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	3518	17	A	N	—	—	—
Distillation Unit	Running	Down	3331	41	A	N	—	—	—
Tank 51	Running	Down	1448	15	A	N	—	—	—
Tank 55	Running	Down	2531	13	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring

Condition D.1.17 Record Keeping Requirements (c)

PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: <u>James Al Gooden</u>	
Date of Inspection: <u>1/8/12</u>	Time: <u>5:00 pm</u>
Shift: (First or Second) <u>FIRST</u>	
Monitor ID: <u>MiniPac 2000</u>	
Instrument Calibration Gases: <u>Isobutylene 100 ppm</u>	
Background Instrument Reading: <u>0.0</u>	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
	Running	Down					Y/N	Date	Time	
Vapor Recovery System:	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	—	—		A	N	—	—	—
CARBON OR FLARE*	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	—	—		A	N	—	—	—
SDS Shredder	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	271	0		A	N	—	—	—
ATDU / OWS	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	1937	2.7	0	A	N	—	—	—
Area 8 -- Tanks 52,53,54 (Tanks 02 through 04)	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	3551	1.5	0	A	N	—	—	—
Distillation Unit	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	3328	4.3	0	A	N	—	—	—
Tank 51	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	1452	1.3	0	A	N	—	—	—
Tank 55	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	2533	1.4	0	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring

Condition D.1.17 Record Keeping Requirements (c)

PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: <u>Rick PALOMO</u>	
Date of Inspection: <u>1/9/12</u>	Time: <u>5:00 AM</u>
Shift: (First or Second) <u>Second</u>	
Monitor ID: <u>Mini Rae 2000</u>	
Instrument Calibration Gases: <u>ISOBUTYLENE 100PPM</u>	
Background Instrument Reading:	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
	Running	Down					Y/N	Date	Time	
Vapor Recovery System:	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	—	—		A	N	—	—	—
CARBON OR FLARE*	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	—	—		A	N	—	—	—
SDS Shredder	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	149	0		A	N	—	—	—
ATDU / OWS	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	1460	4.1	0	A	N	—	—	—
Area 8 -- Tanks 52,53,54 (Tanks 02 through 04)	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	2099	0	2.3	A	N	—	—	—
Distillation Unit	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	3969	6.9	0	A	N	—	—	—
Tank 51	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	2455	0	2.8	A	N	—	—	—
Tank 55	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	1983	4.9	0	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring

Condition D.1.17 Record Keeping Requirements (c)

PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: <u>Jaime N Garcia</u>	
Date of Inspection: <u>1/9/12</u>	Time: <u>5:00 pm</u>
Shift: (First or Second) <u>First</u>	
Monitor ID: <u>MiniRae 2000</u>	
Instrument Calibration Gases: <u>Isobutylene 100 ppm</u>	
Background Instrument Reading: <u>0.6</u>	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
	Running	Down					Y/N	Date	Time	
Vapor Recovery System:	Running	Down	—	—	—	A	N	—	—	—
CARBON OR FLARE*	✓		—	—	—	A	N	—	—	—
SDS Shredder	Running	Down	0	0	—	A	N	—	—	—
ATDU / OWS	Running	Down	514	2.4	0	A	N	—	—	—
Area 8 - - Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	519	1.3	0	A	N	—	—	—
Distillation Unit	Running	Down	1242	4.2	0	A	N	—	—	—
Tank 51	Running	Down	517	4.4	0	A	N	—	—	—
Tank 55	Running	Down	522	4.6	0	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring

Condition D.1.17 Record Keeping Requirements (c)

PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: <u>Rick PALOMO</u>	
Date of Inspection: <u>1/10/12</u>	Time: <u>5:00 AM</u>
Shift: (First or Second) <u>Second</u>	
Monitor ID: <u>Mini Rae 2000</u>	
Instrument Calibration Gases: <u>ISOBUTYLENE 100 PPM</u>	
Background Instrument Reading: <u>0.0</u>	

UNIT DOWN

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
	Running	Down					Y/N	Date	Time	
Vapor Recovery System:	Running	Down	—	—		A	N	—	—	—
CARBON OR FLARE*										
SDS Shredder	Running	Down	137	0		A	N	—	—	—
ATDU / OWS	Running	Down	1688	0	2.3	A	N	—	—	—
Area 8 -- Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	2150	5.7	0	A	N	—	—	—
Distillation Unit	Running	Down	3462	0	6.8	A	N	—	—	—
Tank 51	Running	Down	1988	4.9	0	A	N	—	—	—
Tank 55	Running	Down	1398	0	5.9	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring

Condition D.1.17 Record Keeping Requirements (c)

PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: <u>Ted Compton</u>	
Date of Inspection: <u>1/14/12</u>	Time: <u>500AM</u>
Shift: (First or Second) <u>Second</u>	
Monitor ID: <u>MiniRac 2000</u>	
Instrument Calibration Gases: <u>Isobutylene 100PPM</u>	
Background Instrument Reading: <u>0.0</u>	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust	Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
	Running	Down				Y/N	Date	Time	
Vapor Recovery System:	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	—	—	A	N	—	—	—
CARBON OR <u>FLARE</u>	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	—	—	A	N	—	—	—
SDS Shredder	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	321	0	A	N	—	—	—
ATDU / OWS	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	1968	1.3 0	A	N	—	—	—
Area 8 -- Tanks 52,53,54 (Tanks 02 through 04)	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	2113	2.4 0	A	N	—	—	—
Distillation Unit	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	3210	3.0 0	A	N	—	—	—
Tank 51	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	1557	0.6 0	A	N	—	—	—
Tank 55	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	1926	1.9 0	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring

Condition D.1.17 Record Keeping Requirements (c)

PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: <u>Ted Compton</u>	
Date of Inspection: <u>11/15/12</u>	Time: <u>500 AM</u>
Shift: (First or Second) <u>Second</u>	
Monitor ID: <u>Mini Rea 2000</u>	
Instrument Calibration Gases: <u>Isobutylene 100PPM</u>	
Background Instrument Reading: <u>0.0</u>	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
	Running	Down					Y/N	Date	Time	
Vapor Recovery System:	Running ✓	Down	—	—		A	N	—	—	—
CARBON OR FLARE	Running ✓	Down	366	0		A	N	—	—	—
SDS Shredder	Running ✓	Down	2114	1.6	0	A	N	—	—	—
ATDU / OWS	Running ✓	Down	1981	2.7	0	A	N	—	—	—
Area 8 -- Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	3411	3.3	0	A	N	—	—	—
Distillation Unit	Running ✓	Down	1798	1.2	0	A	N	—	—	—
Tank 51	Running ✓	Down	2219	2.4	0	A	N	—	—	—
Tank 55	Running ✓	Down								

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring

Condition D.1.17 Record Keeping Requirements (c)

PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: <u>Rick PALOMO</u>	
Date of Inspection: <u>1/16/12</u>	Time: <u>5:00</u>
Shift: (First or Second) <u>Second</u>	
Monitor ID: <u>Mini Rae 2000</u>	
Instrument Calibration Gases: <u>ISOBUTYLENE 100PPM</u>	
Background Instrument Reading: <u>0.0</u>	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
	Running	Down					Y/N	Date	Time	
Vapor Recovery System:	<input checked="" type="checkbox"/>	<input type="checkbox"/>	—	—		A	N	—	—	—
CARBON OR FLARE*	<input checked="" type="checkbox"/>	<input type="checkbox"/>	—	—		A	N	—	—	—
SDS Shredder	<input checked="" type="checkbox"/>	<input type="checkbox"/>	137	0		A	N	—	—	—
ATDU / OWS	<input checked="" type="checkbox"/>	<input type="checkbox"/>	1983	0	2.3	A	N	—	—	—
Area 8 -- Tanks 52,53,54 (Tanks 02 through 04)	<input checked="" type="checkbox"/>	<input type="checkbox"/>	2517	1.7	0	A	N	—	—	—
Distillation Unit	<input checked="" type="checkbox"/>	<input type="checkbox"/>	3202	0	4.1	A	N	—	—	—
Tank 51	<input checked="" type="checkbox"/>	<input type="checkbox"/>	2819	1.0	0	A	N	—	—	—
Tank 55	<input checked="" type="checkbox"/>	<input type="checkbox"/>	2419	0	3.0	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring

Condition D.1.17 Record Keeping Requirements (c)

PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: <u>James N. Garcia</u>	
Date of Inspection: <u>1/16/12</u>	Time: <u>5:00 pm</u>
Shift: (First or Second) <u>First</u>	
Monitor ID: <u>MiniPac 2000</u>	
Instrument Calibration Gases: <u>Isobutylene 100 ppm</u>	
Background Instrument Reading: <u>0.0</u>	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust	Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
	Running	Down				Y/N	Date	Time	
Vapor Recovery System:	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	—	—	A	N	—	—	—
CARBON OR FLARE	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	—	—	A	N	—	—	—
SDS Shredder	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	141	0	A	N	—	—	—
ATDU / OWS	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	1980	0 2.5	A	N	—	—	—
Area 8 -- Tanks 52,53,54 (Tanks 02 through 04)	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	2521	1.6 0	A	N	—	—	—
Distillation Unit	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	3205	0 4.3	A	N	—	—	—
Tank 51	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	2823	1.1 0	A	N	—	—	—
Tank 55	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	2416	0 3.3	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring

Condition D.1.17 Record Keeping Requirements (c)

PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: <u>RICK PALOMO</u>	
Date of Inspection: <u>1/17/12</u>	Time: <u>5:00 AM</u>
Shift: (First or Second) <u>Second</u>	
Monitor ID: <u>MiniRae 2000</u>	
Instrument Calibration Gases: <u>ISOBUTYLENE 100PPM</u>	
Background Instrument Reading: <u>0.0</u>	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
	Running	Down					Y/N	Date	Time	
Vapor Recovery System:	<input checked="" type="checkbox"/>	<input type="checkbox"/>	—	—		A	N	—	—	—
CARBON OR FLARE*	<input checked="" type="checkbox"/>	<input type="checkbox"/>	—	—		A	N	—	—	—
SDS Shredder	<input checked="" type="checkbox"/>	<input type="checkbox"/>	137	0		A	N	—	—	—
ATDU / OWS	<input checked="" type="checkbox"/>	<input type="checkbox"/>	1254	0	6.3	A	N	—	—	—
Area 8 -- Tanks 52,53,54 (Tanks 02 through 04)	<input checked="" type="checkbox"/>	<input type="checkbox"/>	1986	1.5	0	A	N	—	—	—
Distillation Unit	<input checked="" type="checkbox"/>	<input type="checkbox"/>	2847	0	2.3	A	N	—	—	—
Tank 51	<input checked="" type="checkbox"/>	<input type="checkbox"/>	3051	3.8	0	A	N	—	—	—
Tank 55	<input checked="" type="checkbox"/>	<input type="checkbox"/>	2471	0	1.8	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring

Condition D.1.17 Record Keeping Requirements (c)

PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: <u>Jaime N Garcia</u>	
Date of Inspection: <u>1/18/12</u>	Time: <u>5:00 pm</u>
Shift: (First or Second) <u>First</u>	
Monitor ID: <u>MiniRae 2000</u>	
Instrument Calibration Gases: <u>Isobutylene 100ppm</u>	
Background Instrument Reading: <u>0.0</u>	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
	Running	Down					Y/N	Date	Time	
Vapor Recovery System:	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	—	—		A	N	—	—	—
CARBON OR FLARE*	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	141	0		A	N	—	—	—
SDS Shredder	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	1983	0	2.3	A	N	—	—	—
ATDU / OWS	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	2527	17	0	A	N	—	—	—
Area 8 -- Tanks 52,53,54 (Tanks 02 through 04)	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	3206	0	4.4	A	N	—	—	—
Distillation Unit	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	2827	1.4	0	A	N	—	—	—
Tank 51	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	2420	0	3.5	A	N	—	—	—
Tank 55	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>								

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring

Condition D.1.17 Record Keeping Requirements (c)

PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: <u>RICK PALOMO</u>	
Date of Inspection: <u>1/18/12</u>	Time: <u>5:00 AM</u>
Shift: (First or Second) <u>Second</u>	
Monitor ID: <u>Mini Rae 2000</u>	
Instrument Calibration Gases: <u>ISOBUTYLENE 100PPM</u>	
Background Instrument Reading: <u>0.0</u>	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
	Running	Down					Y/N	Date	Time	
Vapor Recovery System:	Running ✓	Down	—	—		A	N	—	—	—
CARBON OR FLARE*	Running ✓	Down	104	0		A	N	—	—	—
SDS Shredder	Running ✓	Down	1864	0	2.3	A	N	—	—	—
ATDU / OWS	Running ✓	Down	2051	5.1	0	A	N	—	—	—
Area 8 -- Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	4762	0	289	A	Y	1/18/12	5:00 AM	462
Distillation Unit	Running ✓	Down	1987	2.4	0	A	N	—	—	—
Tank 51	Running ✓	Down	1643	0	5.1	A	N	—	—	—
Tank 55	Running ✓	Down								

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring

Condition D.1.17 Record Keeping Requirements (c)

PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: <u>RICK PALOMO</u>	
Date of Inspection: <u>1/20/12</u>	Time: <u>5:00 AM</u>
Shift: (First or Second) <u>Second</u>	
Monitor ID: <u>MiniRae 2000</u>	
Instrument Calibration Gases: <u>ISOBUTYLENE 100ppm</u>	
Background Instrument Reading: <u>0.0</u>	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
	Running	Down					Y/N	Date	Time	
Vapor Recovery System:	<input checked="" type="checkbox"/>	<input type="checkbox"/>	—	—		A	N	—	—	—
CARBON OR FLARE*	<input checked="" type="checkbox"/>	<input type="checkbox"/>	—	—		A	N	—	—	—
SDS Shredder	<input checked="" type="checkbox"/>	<input type="checkbox"/>	139	0		A	N	—	—	—
ATDU / OWS	<input checked="" type="checkbox"/>	<input type="checkbox"/>	1987	2.3	0	A	N	—	—	—
Area 8 -- Tanks 52,53,54 (Tanks 02 through 04)	<input checked="" type="checkbox"/>	<input type="checkbox"/>	1227	0	4.7	A	N	—	—	—
Distillation Unit	<input checked="" type="checkbox"/>	<input type="checkbox"/>	1783	5.1	0	A	N	—	—	—
Tank 51	<input checked="" type="checkbox"/>	<input type="checkbox"/>	1456	0	2.9	A	N	—	—	—
Tank 55	<input checked="" type="checkbox"/>	<input type="checkbox"/>	1987	8.6	0	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring

Condition D.1.17 Record Keeping Requirements (c)

PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: <u>Ted Compton</u>	
Date of Inspection: <u>11/20/12</u>	Time: <u>1700</u>
Shift: (First or Second) <u>First</u>	
Monitor ID: <u>mini Rae 2000</u>	
Instrument Calibration Gases: <u>Isobutylene 100PPM</u>	
Background Instrument Reading: <u>0.0</u>	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
	Running	Down					Y/N	Date	Time	
Vapor Recovery System:	Running	Down	—	—		A	N	—	—	—
CARBON OR FLARE*	Running	Down	—	—		A	N	—	—	—
SDS Shredder	Running	Down	136	0		A	N	—	—	—
ATDU / OWS	Running	Down	2075	2.7	0	A	N	—	—	—
Area 8 -- Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	2222	0.9	0	A	N	—	—	—
Distillation Unit	Running	Down	3154	0.1	0	A	N	—	—	—
Tank 51	Running	Down	2617	0.6	0	A	N	—	—	—
Tank 55	Running	Down	2149	1.2	0	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring

Condition D.1.17 Record Keeping Requirements (c)

PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: <u>Jaime N. Garcia</u>									
Date of Inspection: <u>1/21/12</u>				Time: <u>5:00 AM</u>					
Shift: (First or Second) <u>Second</u>									
Monitor ID: <u>Mini Rex 2000</u>									
Instrument Calibration Gases: <u>Isobutylene 100ppm</u>									
Background Instrument Reading: <u>0.0</u>									

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
	Running	Down					Y/N	Date	Time	
Vapor Recovery System:	Running	Down				A	N	-	-	
CARBON OR FLARE	✓		0		0	A	N	-	-	
SDS Shredder	Running	Down	146		0	A	N	-	-	
ATDU / OWS	Running	Down	1463	4.3	0	A	N	-	-	
Area 8 -- Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	2107	0	2.4	A	N	-	-	
Distillation Unit	Running	Down	3972	7.1	0	A	N	-	-	
Tank 51	Running	Down	2450	0	2.4	A	N	-	-	
Tank 55	Running	Down	1984	5.1	0	A	N	-	-	

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring

Condition D.1.17 Record Keeping Requirements (c)

PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: <i>Ted Compton</i>									
Date of Inspection: <i>11/21/12</i>				Time: <i>1700</i>					
Shift: (First or Second) <i>First</i>									
Monitor ID: <i>Mini Rac 2000</i>									
Instrument Calibration Gases: <i>Isobutylene 100ppm</i>									
Background Instrument Reading: <i>0.0</i>									

Location of Carbon Control Device	Unit Status		Inlet	Exhaust	Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
	Running	Down				Y/N	Date	Time	
Vapor Recovery System:	Running	Down	—	—	A	N	—	—	—
CARBON OR FLARE*	✓		—	—	A	N	—	—	—
SDS Shredder	Running	Down	<i>142</i>	<i>0</i>	A	N	—	—	—
ATDU / OWS	Running	Down	<i>1926</i>	<i>3.1</i>	<i>0</i>	A	N	—	—
Area 8 -- Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	<i>2441</i>	<i>1.6</i>	<i>0</i>	A	N	—	—
Distillation Unit	Running	Down	<i>2798</i>	<i>0.9</i>	<i>0</i>	A	N	—	—
Tank 51	Running	Down	<i>2776</i>	<i>1.1</i>	<i>0</i>	A	N	—	—
Tank 55	Running	Down	<i>1925</i>	<i>2.2</i>	<i>0</i>	A	N	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)

PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: <u>Jaime N. GARCIA</u>	
Date of Inspection: <u>1/22/12</u>	Time: <u>5:00 pm</u>
Shift: (First or Second) <u>FIRST</u>	
Monitor ID: <u>MiniRae 2000</u>	
Instrument Calibration Gases: <u>Isobutylene 100ppm</u>	
Background Instrument Reading: <u>0.0</u>	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
	Running	Down					Y/N	Date	Time	
Vapor Recovery System:	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	—	—		A	N	—	—	—
CARBON OR FLARE*	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	145	0		A	N	—	—	—
SDS Shredder	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	1930	3.3	0	A	N	—	—	—
ATDU / OWS	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	2443	1.7	0	A	N	—	—	—
Area 8 -- Tanks 52,53,54 (Tanks 02 through 04)	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	3004	.8	0	A	N	—	—	—
Distillation Unit	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	2780	1.3	0	A	N	—	—	—
Tank 51	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	1923	2.4	0	A	N	—	—	—
Tank 55	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>								

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring

Condition D.1.17 Record Keeping Requirements (c)

PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: <u>Ted Compton</u>	
Date of Inspection: <u>1/23/12</u>	Time: <u>1700</u>
Shift: (First or Second) <u>First</u>	
Monitor ID: <u>Mini Rae 2000</u>	
Instrument Calibration Gases: <u>Isobutylene 100ppm</u>	
Background Instrument Reading: <u>0.0</u>	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
	Running	Down					Y/N	Date	Time	
Vapor Recovery System:	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	—	—	—	A	N	—	—	—
CARBON OR <u>FLARE</u>	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	—	—	—	A	N	—	—	—
SDS Shredder	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	152	0	—	A	N	—	—	—
ATDU / OWS	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	1927	0.1	0	A	N	—	—	—
Area 8 -- Tanks 52,53,54 (Tanks 02 through 04)	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	2339	0.3	0	A	N	—	—	—
Distillation Unit	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	2754	2.6	0	A	N	—	—	—
Tank 51	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	1421	1.3	0	A	N	—	—	—
Tank 55	Running <input checked="" type="checkbox"/>	Down <input type="checkbox"/>	2138	1.0	0	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring

Condition D.1.17 Record Keeping Requirements (c)

PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Ted Compton

Date of Inspection: 1/24/12 Time: 1700

Shift: (First or Second) First

Monitor ID: Mini Rac 2000

Instrument Calibration Gases: Isobutylene 100ppm

Background Instrument Reading: 0.0

unit down

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
	Running	Down					Y/N	Date	Time	
Vapor Recovery System:	Running	Down	—	—	—	A	N	—	—	—
CARBON OR FLARE*	Running	Down	0	0	—	A	N	—	—	—
SDS Shredder	Running	Down	163	6.0	0	A	N	—	—	—
ATDU / OWS	Running	Down	2657	1.1	0	A	N	—	—	—
Area 8 -- Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	2911	0.3	0	A	N	—	—	—
Distillation Unit	Running	Down	2222	2.3	0	A	N	—	—	—
Tank 51	Running	Down	1725	1.6	0	A	N	—	—	—
Tank 55	Running	Down								

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND

Condition D.1.10 Carbon Adsorber/Canister Monitoring
 Condition D.1.17 Record Keeping Requirements (c)
 PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Ted Compton
 Date of Inspection: 1/25/12 Time: 1700
 Shift: (First or Second) First
 Monitor ID: Mini Rae 2006
 Instrument Calibration Gases: Isobutylene 100PPM
 Background Instrument Reading: 0.0

unit down

Location of Carbon Control Device	Unit Status		Inlet		Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
	Running	Down						Y/N	Date	Time	
Vapor Recovery System:	Running	Down <input checked="" type="checkbox"/>	—	—	—	—	A	N	—	—	—
CARBON OR FLARE*	Running	Down <input checked="" type="checkbox"/>	0	0	0	0	A	N	—	—	—
SDS Shredder	Running	Down	138	0.6	0	0	A	N	—	—	—
ATDU / OWS	Running	Down	2786	1.1	0	0	A	N	—	—	—
Area 8 -- Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	2213	3.1	0	0	A	N	—	—	—
Distillation Unit	Running	Down	1846	1.7	0	0	A	N	—	—	—
Tank 51	Running	Down	1921	0.9	0	0	A	N	—	—	—
Tank 55	Running	Down									

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)

PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:

Ted Compton

Date of Inspection:

11/26/12

Time:

1700

Shift: (First or Second)

First

Monitor ID:

Mini Rac 2000

Instrument Calibration Gases:

Isobutylene 100PPM

Background Instrument Reading:

0.0

unit down

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
	Running	Down					Y/N	Date	Time	
Vapor Recovery System:	<input checked="" type="checkbox"/>	<input type="checkbox"/>	—	—	—	A	N	—	—	—
CARBON OR FLARE*	<input checked="" type="checkbox"/>	<input type="checkbox"/>	—	—	—	A	N	—	—	—
SDS Shredder	Running	Down	64	0	—	A	N	—	—	—
ATDU / OWS	Running	Down	144	1.2	0	A	N	—	—	—
Area 8 -- Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	2639	1.3	0	A	N	—	—	—
Distillation Unit	Running	Down	1984	3.3	0	A	N	—	—	—
Tank 51	Running	Down	2113	1.6	0	A	N	—	—	—
Tank 55	Running	Down	1813	1.1	0	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
 Condition D.1.17 Record Keeping Requirements (c)
 PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: M. Torres

Date of Inspection: 1-26-12 Time: 6:00 am

Shift: (First or Second) Second

Monitor ID: Mini Pac 2000

Instrument Calibration Gases: Isobutylene 100 ppm

Background Instrument Reading: 0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust	Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
	Running	Down				Y/N	Date	Time	
Vapor Recovery System:	<input checked="" type="checkbox"/>	<input type="checkbox"/>	—	—	A	N	—	—	—
CARBON OR FLARE*	<input checked="" type="checkbox"/>	<input type="checkbox"/>	—	—	A	N	—	—	—
SDS Shredder	<input checked="" type="checkbox"/>	<input type="checkbox"/>	142	0	A	N	—	—	—
ATDU / OWS	<input checked="" type="checkbox"/>	<input type="checkbox"/>	1926	3.1	A	N	—	—	—
Area 8 -- Tanks 52,53,54 (Tanks 02 through 04)	<input checked="" type="checkbox"/>	<input type="checkbox"/>	2444	1.6	A	N	—	—	—
Distillation Unit	<input checked="" type="checkbox"/>	<input type="checkbox"/>	3098	0.9	A	N	—	—	—
Tank 51	<input checked="" type="checkbox"/>	<input type="checkbox"/>	2476	1.1	A	N	—	—	—
Tank 55	<input checked="" type="checkbox"/>	<input type="checkbox"/>	1725	2.2	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)

PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Stoermer

Date of Inspection: 11/27/12

Time: 00500

Shift: (First or Second) Second

Monitor ID: Mini Rae 2000

Instrument Calibration Gases: 100% Isobutylene

Background Instrument Reading: 0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System:	Running	Down	—	—	—	A	N	—	—	—
CARBON OR FLARE*	Running	Down	—	—	—	A	N	—	—	—
SDS Shredder	Running	Down	111	0	—	A	N	—	—	—
ATDU / OWS	Running	Down	983	0	—	A	N	—	—	—
Area 8 -- Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	1134	1.1	0	A	N	—	—	—
Distillation Unit	Running	Down	4721	230	3.9	A	Y	11/27/12	00600	CARBON BOX # 462
Tank 51	Running	Down	1498	0.9	0	A	N	—	—	—
Tank 55	Running	Down	1783	1.0	0	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)

PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Ted Compton

Date of Inspection: 11/27/12

Time: 1700

Shift: (First or Second) First

Monitor ID: Mini Rac 2000

Instrument Calibration Gases: Isobutylene 100ppm

Background Instrument Reading: 0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
	Running	Down					Y/N	Date	Time	
Vapor Recovery System:	Running ✓	Down	—	—	—	A	N	—	—	—
CARBON OR FLARE	Running ✓	Down	103	0	—	A	N	—	—	—
SDS Shredder	Running ✓	Down	1016	0	—	A	N	—	—	—
ATDU / OWS	Running ✓	Down	3997	0.7	0	A	N	—	—	—
Area 8 -- Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	1669	116	2.6	A	N	—	—	—
Distillation Unit	Running ✓	Down	1525	0.4	0	A	N	—	—	—
Tank 51	Running ✓	Down	1601	0.9	0	A	N	—	—	—
Tank 55	Running ✓	Down								

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)

PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Starnes

Date of Inspection: 11/28/12 Time: 0650

Shift: (First or Second) Second

Monitor ID: Mini Pac 2000

Instrument Calibration Gases: 100% isobutylene

Background Instrument Reading: 0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System:	Running	Down	-	-	-	A	2	-	-	-
CARBON OR FLARE*	Running	Down	193	0	-	A	2	-	-	-
SDS Shredder	Running	Down	914	0	-	A	2	-	-	-
ATDU / OWS	Running	Down	1167	0	0	A	2	-	-	-
Area 8 -- Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	5793	3.9	0	A	2	-	-	-
Distillation Unit	Running	Down	1269	1.0	0	A	2	-	-	-
Tank 51	Running	Down	1121	0.9	0	A	2	-	-	-
Tank 55	Running	Down								

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)

PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: <u>RICK PALOMO</u>	
Date of Inspection: <u>1/28/12</u>	Time: <u>5:00 PM</u>
Shift: (First or Second) <u>FIRST</u>	
Monitor ID: <u>Mini Rae 2000</u>	
Instrument Calibration Gases: <u>ISOBUTYLENE 100PPM</u>	
Background Instrument Reading: <u>0.0</u>	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust	Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
	Running	Down				Y/N	Date	Time	
Vapor Recovery System:	<input checked="" type="checkbox"/>	<input type="checkbox"/>	—	—	A	N	—	—	—
CARBON OR FLARE*	<input checked="" type="checkbox"/>	<input type="checkbox"/>	—	—	A	N	—	—	—
SDS Shredder	<input checked="" type="checkbox"/>	<input type="checkbox"/>	132	0	A	N	—	—	—
ATDU / OWS	<input checked="" type="checkbox"/>	<input type="checkbox"/>	1457	0 2.3	A	N	—	—	—
Area 8 -- Tanks 52,53,54 (Tanks 02 through 04)	<input checked="" type="checkbox"/>	<input type="checkbox"/>	1689	1.9 0	A	N	—	—	—
Distillation Unit	<input checked="" type="checkbox"/>	<input type="checkbox"/>	3211	0 7.4	A	N	—	—	—
Tank 51	<input checked="" type="checkbox"/>	<input type="checkbox"/>	1988	5.8 0	A	N	—	—	—
Tank 55	<input checked="" type="checkbox"/>	<input type="checkbox"/>	1764	0 2.1	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)

PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Strayer

Date of Inspection: 11/30/22 Time: @ 0500

Shift: (First or Second) Second

Monitor ID: mini Rae 2000

Instrument Calibration Gases: 100% Iso-butylene

Background Instrument Reading: 0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System:	Running	Down	—	—	—	A	N	—	—	—
CARBON OR FLARE*	Running	Down	277	0	—	A	N	—	—	—
SDS Shredder	Running	Down	843	0	—	A	N	—	—	—
ATDU / OWS	Running	Down	610	.9	0	A	N	—	—	—
Area 8 -- Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	2287	108	0	A	N	—	—	—
Distillation Unit	Running	Down	1957	98	0	A	N	—	—	—
Tank 51	Running	Down	1156	101	0	A	N	—	—	—
Tank 55	Running	Down								

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring

Condition D.1.17 Record Keeping Requirements (c)

PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: RICK PALOMO

Date of Inspection: 1/31/12 Time: 5:00 AM

Shift: (First or Second) Second

Monitor ID: Mini Rge 2000

Instrument Calibration Gases: ISOBUTYLENE 100PPM

Background Instrument Reading: 0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust	Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
	Running	Down				Y/N	Date	Time	
Vapor Recovery System:	<input checked="" type="checkbox"/>	<input type="checkbox"/>	—	—	A	N	—	—	—
CARBON OR FLARE*	<input checked="" type="checkbox"/>	<input type="checkbox"/>	—	—	A	N	—	—	—
SDS Shredder	<input checked="" type="checkbox"/>	<input type="checkbox"/>	139	0	A	N	—	—	—
ATDU / OWS	<input checked="" type="checkbox"/>	<input type="checkbox"/>	4376	0 398	A	Y	1/31/12	5:00 AM	462
Area 8 -- Tanks 52,53,54 (Tanks 02 through 04)	<input checked="" type="checkbox"/>	<input type="checkbox"/>	1987	7.9 0	A	N	—	—	—
Distillation Unit	<input checked="" type="checkbox"/>	<input type="checkbox"/>	4051	0 2.8	A	N	—	—	—
Tank 51	<input checked="" type="checkbox"/>	<input type="checkbox"/>	3287	4.1 0	A	N	—	—	—
Tank 55	<input checked="" type="checkbox"/>	<input type="checkbox"/>	1988	0 2.3	A	N	—	—	—